

Application No. 10/055836
Page 2

Amendment
Attorney Docket No. S63.2B-10059-US01

Amendments To The Claims:

1. (Withdrawn) A removable loading tool for use with a catheter assembly, the loading tool comprising:

a body, the body defining a substantially hollow chamber, the substantially hollow chamber having a first portion and a second portion, the first portion having a first diameter sized to contain at least a portion of the catheter assembly having a stent mounted thereon, the second portion having a second diameter less than that of the first diameter, the body constructed and arranged to protect the at least a portion of the catheter assembly and the stent from undesired contact or damage during loading of a guide wire into the catheter assembly.

2. (Withdrawn) The loading tool of claim 1 wherein the first portion of the substantially hollow chamber defines a first opening and the second portion of the substantially hollow chamber comprises a second opening, the first opening having a diameter sufficient to allow passage of the catheter assembly having the stent mounted thereon, the second opening having a diameter smaller than the first opening, the diameter of the second opening being sufficient to allow passage of a proximal shaft of the catheter assembly.

3. (Withdrawn) The loading tool of claim 1 further comprising a neck portion the neck portion connecting the first portion of the substantially hollow chamber to the second portion of the substantially hollow chamber.

4. (Withdrawn) The loading tool of claim 3 wherein the neck portion defines a neck portion diameter, the neck portion diameter tapering from the first diameter to the second diameter.

5. (Withdrawn) The loading tool of claim 3 wherein the neck portion is constructed and arranged to engage the at least a portion of a catheter assembly having a stent mounted thereon, thereby preventing the at least a portion of a catheter assembly having a stent mounted thereon from migrating from the first portion of the hollow chamber to the second portion of the hollow chamber.

6. (Withdrawn) The loading tool of claim 1 wherein the body is constructed from at least one material of the group consisting of: metal, polymer and any combination thereof.

Application No. 10/055836
Page 3

Amendment
Attorney Docket No. S63.2B-10059-US01

7. (Withdrawn) The loading tool of claim 1 further comprising an inside surface, the inside surface being immediately adjacent to the body and defining at least the first portion of the substantially hollow chamber, the inside surface comprising a polymer material, the polymer material constructed and arranged to protect the stent from damage during manipulation of the catheter assembly.
8. (Withdrawn) The loading tool of claim 7 wherein the body is constructed from a different material than the inside surface.
9. (Withdrawn) The loading tool of claim 7 wherein the body is constructed from a the same material as the inside surface.
10. (Withdrawn) The loading tool of claim 7 wherein the stent is a drug delivery stent, the polymer material being inert relative to a drug being delivered by the drug delivery stent.
11. (Withdrawn) The loading tool of claim 7 wherein the polymer material is characterized as being lubricious.
12. (Withdrawn) The loading tool of claim 1 wherein the body further comprises a gripping surface, the gripping surface comprising at least one surface feature of a portion of an external surface of the body, the gripping surface selected from at least one surface feature of the group consisting of, a textured surface, a surface coating and any combination thereof.
13. (Withdrawn) The loading tool of claim 1 wherein the body further comprises a first half and a second half, the first half and the second half being separable from one another.
14. (Withdrawn) The loading tool of claim 13 wherein the first half and the second half are separable along a common seam, the first half being hingedly connected to the second half along at least a portion of one side of the common seam, the first half and the second half being constructed and arranged to hingedly move between an open position and a closed position.
15. (Withdrawn) The loading tool of claim 13 wherein the first half and the second half define the substantially hollow chamber in the closed position.
16. (Withdrawn) The loading tool of claim 13 wherein in the open position the first half and the second half are engaged along only one side of the common seam.
17. (Withdrawn) The loading tool of claim 13 further comprising at least one fastening device, the at least one fastening device, the at least one fastening device removably engaging the first half to the second half in the closed position.

Application No. 10/055836
Page 4

Amendment
Attorney Docket No. S63.2B-10059-US01

18. (Withdrawn) The loading tool of claim 16 wherein the at least one fastening device is selected from at least one member of the group consisting of: at least one fastener, at least one screw, at least one tab, at least one clip and any combination thereof.

19. (Withdrawn) The loading tool of claim 1 wherein the first diameter is about 0.5 mm to about 5 mm.

20. (Withdrawn) The loading tool of claim 1 wherein the first diameter is about 0.7 mm to about 3.8 mm.

21. (Withdrawn) The loading tool of claim 1 wherein the second diameter is about 0.2 mm to about 4.9 mm.

22. (Withdrawn) The loading tool of claim 1 wherein the second diameter is about 0.4 mm to about 4.5 mm.

23. (Currently Amended) A catheter assembly comprising:

a catheter, the catheter having a catheter body defining a guide wire lumen, a proximal region and a distal region;

a stent, the stent being disposed about at least a portion of the distal region of the catheter body, the at least a portion of the distal region of the catheter body and stent defining a first diameter region of the assembly and at least a portion of the proximal region adjacent to the distal region defining a second diameter region of the assembly, the first diameter region having an outer diameter greater than that of the second diameter region;

a removable guide wire loading tool, the tool being disposed about the at least a portion of the distal region of the catheter and at least a portion of the proximal region of the catheter, the tool having a tool body, the tool body defining a substantially hollow chamber, the chamber having an inner surface region, the inner surface region defining a first portion removably containing the first diameter region and a second portion removably containing the second diameter region, the first portion having an inner diameter greater than that of the second portion;

the inner surface region further defining a substantially hollow neck portion in fluid communication with the first portion of the substantially hollow chamber and the second portion of the substantially hollow chamber, the neck portion comprising a neck portion

Application No. 10/055836
Page 5

Amendment
Attorney Docket No. S63.2B-10059-US01

diameter, the neck portion diameter tapering from the inner diameter of the first portion to the inner diameter of the second portion.

24. (Cancelled)

25. (Currently Amended) The catheter assembly of claim 24-23 wherein the tool body is constructed and arranged to protect the stent positioned on the at least a portion of the distal region of the catheter from undesired contact or damage during loading of a guide wire into the guide wire lumen.

26. (Currently Amended) The catheter assembly of claim 24-23 wherein the tool body is constructed and arranged to protect the stent from undesired contact or damage during loading of a guide wire into the guide wire lumen.

27. (Previously Presented) The catheter assembly of claim 23 wherein at least a portion of the stent comprises a coating, the coating is selected from at least one member of the group consisting of: drugs, genetic material, cells, a non-genetic therapeutic agent, a polymer matrix having a therapeutic component, and any combination thereof.

28. (Cancelled)

29. (Previously Presented) The catheter assembly of claim 23 wherein the first portion of the substantially hollow chamber defines a first opening and the second portion of the substantially hollow chamber comprises a second opening, the first opening having a diameter sufficient to allow passage of the catheter assembly having the stent mounted thereon, the second opening having a diameter smaller than the first opening, the diameter of the second opening being sufficient to allow passage of a proximal shaft of the catheter assembly.

30. (Cancelled)

31. (Cancelled)

32. (Previously Presented) The catheter assembly of claim 30 wherein the neck portion is constructed and arranged to engage the at least a portion of the distal region of the catheter body, thereby preventing the at least a portion of the distal region of the catheter body and stent from migrating from the first portion of the hollow chamber to the second portion of the hollow chamber.

33. (Previously Presented) The catheter assembly of claim 23 wherein the tool body is constructed from at least one material of the group consisting of: metal, polymer and any

Application No. 10/055836
Page 6

Amendment
Attorney Docket No. S63.2B-10059-US01

combination thereof.

34. (Previously Presented) The catheter assembly of claim 23 wherein the inner surface region corresponding to at least the first portion of the chamber comprises a polymer material, the polymer material constructed and arranged to protect the stent from damage during manipulation of the catheter assembly.

35. (Previously Presented) The catheter assembly of claim 34 wherein the body is constructed from a different material than the inner surface region.

36. (Previously Presented) The catheter assembly of claim 34 wherein the body is constructed from a the same material as the inner surface region.

37. (Previously Presented) The catheter assembly of claim 34 wherein the stent is a drug delivery stent, the polymer material being inert relative to a drug being delivered by the drug delivery stent.

38. (Previously Presented) The catheter assembly of claim 34 wherein the polymer material is characterized as being lubricious.

39. (Previously Presented) The catheter assembly of claim 23 wherein the body further comprises a gripping surface, the gripping surface selected from at least one surface feature of the group consisting of, a textured surface, a surface coating and any combination thereof.

40. (Previously Presented) The catheter assembly of claim 23 wherein the inner diameter of the first portion of the inner surface region is about 0.5 mm to about 5 mm.

41. (Previously Presented) The catheter assembly of claim 23 wherein the inner diameter of the first portion of the inner surface region is about 0.7 mm to about 3.8 mm.

42. (Previously Presented) The catheter assembly of claim 23 wherein the inner diameter of the second portion of the inner surface region is about 0.2 mm to about 4.9 mm.

43. (Withdrawn) The catheter assembly of claim 1 wherein the inner diameter of the second portion of the inner surface region is about 0.4 mm to about 4.5 mm.